



TA17X 50Hz POWERED BY FAWDE SERIES



TECHNICAL SPECIFICATIONS

DIESEL GENERATING SET 400/230V-50Hz-3Phase

Model	TA17X	
Power(ESP)	kVA/kw	17/13.2
Power(PRP)	kVA/kw	15/12
Starter Voltage	V	400/230
Rated Current	A	24
Rated rotation speed	r/min	1500
Power Factor		0.8
Fuel Consumption	g/KWh	240
Fuel Tank Capacity	Litre	158
Noise level	dB(A)@7m	75

WEIGHT AND DIMENSIONS

GEN-Set	Dimension (L*W*H)	Weight
Open Type	1500mm×780mm×1136mm	750Kg

STANDARDS:

Genset: GB/T2820—2009,ISO8528

Alternator: CEDEX, CX12.8

Diesel Engine: FAWDE, 4DW81-23D

Standby Power: Continues running at variable load for duration of an emergency. No overload is permitted on these ratings.

Prime Power: Continues running at variable load for unlimited periods with 10% overload available for 1 hour in any 12 hour period.

CONFIGURATION:

Standard: Engine, alternator, cooling system, Base frame (excluding fuel tank), shock absorber, air inlet system, control box (including mains floating charge), plastic fan blades (when the engine and water tank do not bring).

Optional: Base frame (including fuel tank), water jacket heater, fuel water separator, fuel heater, fuel level sensor (only supporting underframe tank), switch box (with switch), power switch, the water level sensor, motor anti condensation heater, automatic fueling system (only supporting base frame including fuel tank), battery frame.

Accessories: Silencer, bellow, exhaust silencing system accessories (with the matching engine), regular battery, starting cord assembly, data of gen-set, random tool (with the matching engine).





ENGINE Specification

Manufacturer: FAWDE	
Model	4DW81-23D
Engine speed Rated	1500 RPM
Cylinder /Arrangement	4/ L
Displacement	2.27 L
Bore and Stroke	85 mm×100 mm
Compression ratio	17 : 1
Max. stand by power at rated RPM	19 KW
Frequency regulation , steady state	≤5%
Governor : type	Electric/mechanical
Aspiration and Cooling	Naturally aspirated, water cool

Exhaust System

Exhaust gas flow	4.2m³/min
Exhaust temperature	550°C
Energy to exhaust	17.2kw

Fuel System

Fuel consumption100% (of the Prime Power)	240g/KWh
Fuel consumption75% (of the Prime Power)	
Fuel consumption50% (of the Prime Power)	
Fuel consumption25% (of the Prime Power)	

Oil system

Total oil capacity w/filter s	7.8L
-------------------------------	------



- FAWDE engines with optimized design, easy maintenance, big power density, with stable performance, reliable and durable.
- Low fuel consumption and emission, lower noise and smooth running.
- Parts commonality, seriation of engine application.
- Compact structure, easy maintenance.

Note: All data sheets are for reference only and subject to change without prior notice.





ALTERNATOR Specification

Manufacturer: CEDEX

Type	CX12.8
Number of phase power	3
Factor (Cos Phi)	0.8
Pole	4
Bearing	1
Coupling	Direct
Exciter type	Brushless SHUNT
Insulation : class , temperature rise	H / H
Degree of protection	IP23
Altitude	≤1000m
Winding Pitch	2/3
Winding Leads	6/12

FEATURES

- Class H insulation system
- selectable winding, To meet the demand of the bad environment
- 12 Lead Reconnect, able for different voltage, meet the demand of different countries and regions
- 2/3 pitch windings restrain the content of harmonious
- Different Excitation Systems for different load demand
- Ip23 standard protection, IP44 for option
- Provide single bearing or double bearing




STANDARDS

-IEC60034, NEMA MG1-32, ISO8528, CSA
C22.2-100, VDE 0530, GB755

Note: All data sheets are for reference only and subject to change without prior notice.



Control Panel

Model: DSE 6020

AUTO START & AUTO MAINS FAILURE CONTROL MODULES

DIMENSIONS

OVERALL

216mm x 158mm x 42mm
(8.5" x 6.2" x 1.6")

PANEL CUTOUT

182mm x 137mm
(7.2" x 5.4")

WEIGHT

400g (0.4kg)



- | | | |
|---|--|---|
| <p>KEY FEATURES</p> <ul style="list-style-type: none"> ➤ Back-lit icon LCD display ➤ Front panel editing ➤ LED and LCD alarm indication ➤ Power Save mode ➤ CAN and Magnetic Pick-up/Alt. versions available (specify on ordering) ➤ PC and front panel configuration ➤ 4 Digital inputs ➤ 3 Analogue inputs ➤ 6 Outputs (4 configurable on Magnetic Pick-up/Alt., 6 configurable on CAN version) ➤ Configurable timers and alarms ➤ Alternative configuration ➤ Event Log (5) ➤ Remote Start input ➤ 3 Phase generator monitoring | <ul style="list-style-type: none"> ➤ Current monitoring and protection ➤ Power monitoring(kW, kV A, kV Ar) ➤ 3 Phase Mains (Utility) monitoring (DSE6020 only) ➤ Test button (DSE6020 only) ➤ Battery Voltage monitoring ➤ Engine pre-heat ➤ Hours counter ➤ Comprehensive shutdown or warning on fault condition <p>KEY BENEFITS</p> <ul style="list-style-type: none"> ➤ Automatically transfers between mains (utility) and generator power (DSE6020 only) ➤ Hours counter provides accurate information for monitoring and maintenance periods ➤ User-friendly set-up and button | <ul style="list-style-type: none"> ➤ Multiple engine parameters are monitored simultaneously ➤ Module can be configured to suit individual applications ➤ Compatible with a wide range of CAN engines ➤ Uses DSE Configuration Suite PC software for simplified configuration ➤ IP65 rating (with optional gasket) offers increased resistance to water ingress ➤ Licence-free PC software. |
|---|--|---|



ENERGO RESURS

Engineering company - distribution Russian Federation

123317, Москва, Пресненская набережная, д. 6, стр. 2
ОГРН 1177746973205, ИНН 7716869588, КПП 771601001

Тел. 8-800-100-56-71 e-mail: resurs.e@inbox.ru www.genresurs.ru